

Fall Protection Quiz

Workplace Safety > Fall Protection Quiz > Question

- Over 800 construction workers die each year while on the job. How many of these deaths are due to falls?
(A) 1 of every 2 (B) **1 of every 3** (C) 1 of every 5 (D) 1 of every 7 (E) 1 of every 10
- Who is primarily responsible for providing employees with a fall protection system?
(A) The manufacturer of the fall protection system
(B) **The employer**
(C) The employee
(D) The insurer
- A fall arrest system is required when a worker is operating at a height of...
(A) 3 feet or more
(B) **6 feet or more**
(C) 10 feet or more
(D) None of the above
- OSHA requires that fall protection be provided at elevations of four feet in general industry workplaces, five feet in shipyards, six feet in the construction industry and eight feet in long shoring operations. These same requirements above apply to dangerous equipment and machinery.
(A) True
(B) **False**
- When should ladders be inspected?
(A) **Each day before use**
(B) At least once a week
(C) At least once a month
(D) At least once a year

6. The angle of the ladder should be so that the ladder's base is one foot out from the ledge for each four feet of a ladder's height.

(A) True

(B) False

7. When using a ladder to climb a roof, the ladder must extend at least___ above it.

(A) 18 inches

(B) 24 inches

(C) 30 inches

(D) 36 inches

8. Manhole steps and step bolts must be checked for

(A) Sharp corners, protruding objects, and burrs

(B) Bent step bolts

(C) Corrosion

(D) All of the above

9. what height must fall protection be provided for in the construction industry?

(A) 3 feet

(B) 5 feet

(C) 6 feet

(D) 8 feet

10. Step bolts that are bent at an angle greater than 15 degrees below horizontal should be removed and replaced.

(A) True

(B) False